



#### Features & Benefits

- Suitable for Gigabit Ethernet applications
- Individual colour coded saddles allow quick and accurate terminations
- Top quality sockets
- Fully QA tested
- Optional cable management tray

#### Specifications

Width	483 mm (19")
Depth	30 mm
Height	1u (44 mm)
Fixing Centres	467 mm
Material	Mild steel sheet CR4 to BSEN 10130-1999 DC01 Plastic inserts ABS thermoplastic resin with grade UL94 V0 at 1.5 mm flame retardancy
Finish	Black powder coated to BS6496
Socket Labels	9 mm numbered card to BS6496
IDC Labels	Individual colour coded labels to T568B
Cable Guide	Individual cabling saddles with cable tie positioned for left or right entry
IDC Blocks	4-way industry standard IDC blocks
PCB	Groups of 4 identical circuits on 1.6 mm double sided PTH boards
Conforms to	ANSI/TIA-568-C Enhanced Category 5 Specification

Connectix Enhanced Category 5 High Density Elite Patch Panels provide exceptional performance for high speed LANs including Gigabit Ethernet applications. The High-Density format is ideal where cabinet space is at a premium.

The panels achieve optimum transmission performances by incorporating the highest quality components and innovative on-board compensation techniques. The front of the panel features easy to use slide in labels and the rear utilises colour coded cable saddles and hook and loop cable retainers.

All Connectix Enhanced Category 5 Panels offer extended PowerSum characteristics and exceed the ANSI/TIA-568-C specifications, and when combined with Connectix Enhanced Category 5 Modules and UTP Cable, the link will perform well in excess of the Enhanced Category 5 Specification.

#### Ordering Information

Product Description	Part Number
CCS Elite Cat 5e 24 Way UTP Panel	009-001-009-09
CCS Elite Cat 5e 48 Way UTP Panel	009-001-009-20
CCS Elite Cable Management Tray	009-001-008-30

